

BALLISTIC GOGGLES

bolle
TACTICAL
www.bolle-tactical.com

X1000 DUAL LENS

Low profile double ballistic lens, the X1000 dual lens offers the best antifog resistance. Featuring equalizer technology which uses a waterproof, breathable vent to eliminate any moisture. The result is distortion free vision and no fogging at any altitude. With the X1000 dual lens, you will be completely protected and prepared for any situation.

PANORAMIC FIELD OF VISION

EQUALIZER TECHNOLOGY

ANTI-SCRATCH, ANTI-FOG COATINGS

DOUBLE PC HIGH BALLISTIC LENS



PIVOT FOR HELMET WEARERS

QUICK RELEASE SYSTEM

VENTILATION

HIGH HEAT RESISTANCE TPV FRAME




120 G

Europe Bollé Safety
95 Rue Louis Guérin
69100 Villeurbanne - France
tel: 00 33 (0) 4 78 85 23 64
fax: 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com




U.K. Bollé Safety
Unit C83 - Barwell Business Park
Leatherhead Road - Chessington
Surrey - KT9 2NY
tel. 00 44 (0)208 391 4700
fax 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

Ballistic Resistance STANAG 2920

Clear lens: V50 275 m/s (990 km/h)
Smoke lens: V50 272 m/s (979 km/h)
Yellow lens: V50 265 m/s (954 km/h)



Version and options

-  - SPARE LENSES OPTION:
-  - CLEAR, YELLOW AND SMOKE
-  LENSES

RX INSERT

SUPPLY WITH: MICROFIBER POUCH AROUND THE STRAP /
INDIVIDUAL RIGID CARRY CASE



X1000 DUAL LENS

Safety goggles

STANDARDS MARKINGS :

| Products ref. | LENSES | | | | | | | | | | | | FRAMES | | | | | | | | | | | | | |
|---------------|------------------------------|--------------------------|-----------------------|-----------------|-------------------|--------------|--------------------------|------------------------------|----------------------------|----------------------------|-------------------------------|---|--------------|---------|-----------------------|-----------|----------------|--------------|----------------------------------|---|-------------------------------|--------------------------|------------------------------|----------------------------|---------|----------------------------|
| | Risks relating to radiations | | Bollé Protection logo | Optical quality | | | Mechanical Risks | | | Electrical Risks | Thermal Risks | Coatings (Optional marking K: anti-scratch N: anti-fog) | | CE logo | Bollé Protection logo | Standards | Chemical Risks | | | Electrical Risks | Mechanical Risks | | | Thermal Risks | CE logo | |
| | EN 170 - UV | EN 172 - Solar (100% UV) | | Permanent wear | Intermittent wear | Short period | Low energy impact 45 m/s | Medium energy impact 120 m/s | High energy impact 190 m/s | Extreme temperature impact | Electric arc short circuiting | Molten metals and hot solids | anti-scratch | | | | anti-fog | Liquid drops | Large dust particles > 5 microns | Gas and fine dust particles < 5 microns | Electric arc short circuiting | Low energy impact 45 m/s | Medium energy impact 120 m/s | High energy impact 190 m/s | | Extreme temperature impact |
| X1NDEI | 2C-1,2 | | | 1 | | | B | N/A | T | N/A | N/A | K | N | | | EN 166 | 3 | | | | N/A | B | N/A | T | N/A | |
| FAX1DEI | 2C-1,2 | | | 1 | | | B | N/A | T | N/A | N/A | K | N | | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| FAX1DEJ | 2C-1,2 | | | 1 | | | B | N/A | T | N/A | N/A | K | N | | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| FAX1DEF | | 5-2,5 | | 1 | | | B | N/A | T | N/A | N/A | K | N | | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |

N/A: Non Authorized in the standards



Résistance Balistique
STANAG 2920

PACKAGING AND EAN 13 CODE :

| | X1NDEI |
|--|---------------|
| <input checked="" type="checkbox"/> individual plastic bag | 3660740005740 |
| <input checked="" type="checkbox"/> N/A | N/A |
| <input checked="" type="checkbox"/> 60 safety goggles per outer pack | 3660740205744 |



V50 : 979 km/h (272 m/s)

V50 : 954 km/h (265 m/s)



FAX1DEJ

CHARACTERISTICS :

| | |
|--------------|--|
| Face | Ballistic outer lens: 2.95mm, anti-scratch - Curve 4.5 Ballistic inner lens: 1.3mm, anti-fog - Curve 5.75 |
| Frame | Black TPV Available in black, sand and nato green |
| Spare Lenses | Clear, yellow and smoke tints |
| Strap | Adjustable, 40 mm wide with non-slip technology |
| Foam | No |

PACKAGING AND EAN 13 CODE :

| | FAX1DEI | FAX1DEJ | FAX1DEF |
|---|---------------|---------------|---------------|
| <input checked="" type="checkbox"/> individual plastic bag | 3660740005757 | 3660740005764 | 3660740005771 |
| <input checked="" type="checkbox"/> 15 spare lenses per box | 3660740105754 | 3660740105761 | 3660740105778 |
| 150 spare lenses per outer pack | 3660740205751 | 3660740205768 | 3660740205775 |

Notified laboratories for certification :



Banc Officiel d'Epreuve Saint-Etienne

